

SPECIFICATION SHEET



DESCRIPTION 90 5004

- 13G HPPE/steel cut resistant gloves, with PU palm coating

FEATURES AND BENEFITS

- Durable HPPE knitting with excellent cut resistance
- Anti-abrasion & anti-slip
- High performance cut resistant level secure against mechanical hazards
- Light PU coating with good grip and excellent touch



APPLICATIONS

- Metal & Glass Handling
- Sharp small parts handling
- Automotive industry
- Wood working
- Sanitation&Recycling
- Transportation
- Warehousing
- Construction
- General maintenance

CARE INSTRUCTIONS

- Machine wash in warm water with Detergent and Bleach. Rinse well and spin extract using high speed. Tumble dry on Low heat setting. Proper washing will inhibit odors caused by the growth of bacteria or mold.

EN388



XXXXXX

- Abrasion resistance
- Blade cut resistance
- Tear strength resistance
- Puncture resistance
- Cut Resistance method (EN ISO 13997)

TECHNICAL DATA

| | | | | | |
|-----------------|---|-----|-----|-------|--------|
| Description | 13G HPPE/steel cut resistant gloves, with PU palm coating | | | | |
| Materials | Liner: HPPE knit | | | | |
| | Coating: PU palm coating | | | | |
| Cuff Style | Elastic seamless knit | | | | |
| Color | Grey,Green,Blue... | | | | |
| Size | 7/S | 8/M | 9/L | 10/XL | 11/XXL |
| Length (cm) | 23 | 24 | 25 | 26 | 27 |
| Palm width (cm) | 9 | 9.5 | 10 | 10.5 | 11 |
| Packing | Printing logo, 12 pairs per bag,120 pairs per case | | | | |

Tolerance: ±5mm

STANDARDS

- CE CATEGORY: II Intermediary risk in accordance with:
- EN 420 / AS / NZS2161.2:2016 General Requirements
- EN 388 / AS / NZS2161.3:2016 Protection Against Mechanical Risks