SPECIFICATION SHEET



DESCRIPTION 90 5012

• 13G HPPE cut resistant gloves, with sandy nitrile palm coating

FEATURES AND BENEFITS

- Durable HPPE knitting with excellent cut resistance
- Anti-abrasion & anti-slip
- High performance cut resistant level secure against mechanical hazards
- Sandy finished coating with exellent grip in wet and oil environments



- Metal & Glass Handling
- · Sharp small parts handling
- Automotive industry
- Wood working
- Sanitation&Recycling
- Transportation
- Warehousing
- Construction
- General maintenance

XXXXX Abrasion resistance Blade cut resistance

Abrasion resistance
Blade cut resistance
Tear strength resistance
Punture resistance
Cut Resistance method (EN ISO 13997)

CARE INSTRUCTIONS

Machine wash in warm water with Detergent and Bleach. Rinse
well and spin extract using high speed. Tumble dry on Low
heat setting. Proper washing will inhibit odors caused by
the growth of bacteria or mold.

TECHNICAL DATA

Description	13G HPPE cut resistant gloves, with sandy nitrile palm coating				
Materials	Liner: HPPE knit				
	Coating: Sandy nitrile palm coating				
Cuff Style	Elastic seamless knit				
Color	Grey,Green,Blue				
Size	7/S	8/M	9/L	10/XL	11/XXL
Length (cm)	23	24	25	26	27
Palm width	9	9.5	10	10.5	11
(cm)	9	9.0	10	10.5	''
Packing	Printing logo, 12 pairs per bag,120 pairs per case				

Tolerance: ±5mm

STANDARDS

- CE CATEGORY: II Intermediary risk in accordance with:
- EN 420 / AS / NZS2161.2:2016 General Requirements
- EN 388 / AS / NZS2161.3:2016 Protection Against Mechanical Risks