

# SPECIFICATION SHEET



## DESCRIPTION 90 5006

- 13G HPPE cut resistant gloves, with sandy nitrile palm coating reinforcement at thumb crotch

## FEATURES AND BENEFITS

- Durable HPPE knitting with excellent cut resistance
- Anti-abrasion & anti-slip
- High performance cut resistant level secure against mechanical hazards
- Sandy finished coating with excellent grip in wet and oil environments

## APPLICATIONS

- Metal & Glass Handling
- Sharp small parts handling
- Automotive industry
- Wood working
- Sanitation&Recycling
- Transportation
- Warehousing
- Construction
- General maintenance

## CARE INSTRUCTIONS

- Machine wash in warm water with Detergent and Bleach. Rinse well and spin extract using high speed. Tumble dry on Low heat setting. Proper washing will inhibit odors caused by the growth of bacteria or mold.



EN388



XXXXX

- Abrasion resistance
- Blade cut resistance
- Tear strength resistance
- Puncture resistance
- Cut Resistance method (EN ISO 13997)

## TECHNICAL DATA

Description	13G HPPE cut resistant gloves, with sandy nitrile palm coating, reinforcement at thumb crotch				
Materials	Liner: HPPE knit Coating: sandy nitrile palm coating, reinforcement at thumb crotch				
Cuff Style	Elastic seamless knit				
Color	Grey, Yellow, Green...				
Size	7/S	8/M	9/L	10/XL	11/XXL
Length (cm)	23	24	25	26	27
Palm width (cm)	9	9.5	10	10.5	11
Packing	Printing logo, 12 pairs per bag, 120 pairs per case				

Tolerance: ±5mm

## STANDARDS

- CE CATEGORY: II Intermediary risk in accordance with:
- EN 420 / AS / NZS2161.2:2016 General Requirements
- EN 388 / AS / NZS2161.3:2016 Protection Against Mechanical Risks