

SPECIFICATION SHEET



DESCRIPTION 90 1011

- 13G HI-VIS yellow polyester gloves, with grey PU palm coating

FEATURES AND BENEFITS

- Light & Soft fabric
- Breathable knitting back
- Anti-abrasion & Anti-slip
- Soft & Comfortable hand feeling



APPLICATIONS

- Gardening
- Warehousing
- Construction
- Laboratory
- Electronic Industry
- General Maintenance

CARE INSTRUCTIONS

- Machine wash in warm water with Detergent and Bleach. Rinse well and spin extract using high speed. Tumble dry on Low heat setting. Proper washing will inhibit odors caused by the growth of bacteria or mold.

EN388



XXXXXX

| | |
|--------|--------------------------------------|
| XXXXXX | Abrasion resistance |
| XXXXXX | Blade cut resistance |
| XXXXXX | Tear strength resistance |
| XXXXXX | Puncture resistance |
| XXXXXX | Cut Resistance method (EN ISO 13997) |

TECHNICAL DATA

| | | | | | |
|-------------|---|-----|-----|-------|--------|
| Description | 13G HI-VIS yellow polyester gloves, with grey PU palm coating | | | | |
| Materials | Liner: polyester knit | | | | |
| | Coating: PU coated palm | | | | |
| Cuff Style | Elastic seamless knit | | | | |
| Color | White,Grey,Black,Red.... | | | | |
| Size | 7/S | 8/M | 9/L | 10/XL | 11/XXL |
| Length (cm) | 22 | 23 | 24 | 25 | 26 |
| Packing | Printing logo, 12 pairs per bag,120 pairs per case | | | | |

Tolerance: ±5mm

STANDARDS

- CE CATEGORY: II Intermediary risk in accordance with:
- EN 420 / AS / NZS2161.2:2016 General Requirements
- EN 388 / AS / NZS2161.3:2016 Protection Against Mechanical Risks