

SPECIFICATION SHEET



DESCRIPTION 90 5019

- 13G aramid/spendex gloves, with black foam nitrile palm coating

FEATURES AND BENEFITS

- Durable HPPE knitting with excellent cut resistance
- Anti-abrasion & anti-slip
- High performance cut resistant level secure against mechanical hazards
- Sandy finished coating with excellent grip in wet and oil environments

APPLICATIONS

- Metal & Glass Handling
- Sharp small parts handling
- Automotive industry
- Wood working
- Sanitation&Recycling
- Transportation
- Warehousing
- Construction
- General maintenance



EN388



XXXXXX

- Abrasion resistance
- Blade cut resistance
- Tear strength resistance
- Puncture resistance
- Cut Resistance method (EN ISO 13997)

CARE INSTRUCTIONS

- Machine wash in warm water with Detergent and Bleach. Rinse well and spin extract using high speed. Tumble dry on Low heat setting. Proper washing will inhibit odors caused by the growth of bacteria or mold.

TECHNICAL DATA

| | | | | | |
|-----------------|---|-----|-----|-------|--------|
| Description | 13G aramid/spendex gloves, with black foam nitrile palm coating | | | | |
| Materials | Liner: HPPE knit | | | | |
| | Coating: foam nitrile dipping | | | | |
| Cuff Style | Elastic seamless knit | | | | |
| Color | Grey,Green,Blue... | | | | |
| Size | 7/S | 8/M | 9/L | 10/XL | 11/XXL |
| Length (cm) | 23 | 24 | 25 | 26 | 27 |
| Palm width (cm) | 9 | 9.5 | 10 | 10.5 | 11 |
| Packing | Printing logo, 12 pairs per bag,120 pairs per case | | | | |

Tolerance: ±5mm

STANDARDS

- CE CATEGORY: II Intermediary risk in accordance with:
- EN 420 / AS / NZS2161.2:2016 General Requirements
- EN 388 / AS / NZS2161.3:2016 Protection Against Mechanical Risks