

SPECIFICATION SHEET



DESCRIPTION 90 7002

- 13G HPPE cut resistant gloves, with black sandy palm coating,TPR on back

FEATURES AND BENEFITS

- Durable HPPE knitting with excellent cut resistance
- Special anti-abrasion patch sewed on palm & thumb crotch enhance the puncture level and durability
- High performance cut resistant level secure against mechanical hazard
- Sandy finished coating with excellent grip in wet and oil environments



APPLICATIONS

- Metal & Glass Handling
- Sharp small parts handling
- Automotive industry
- Wood working
- Sanitation&Recycling
- Transportation
- Warehousing
- General maintenance
- Mechanical Operation

CARE INSTRUCTIONS

- Machine wash in warm water with Detergent and Bleach. Rinse well and spin extract using high speed. Tumble dry on Low heat setting. Proper washing will inhibit odors caused by the growth of bacteria or mold.

EN388



XXXXX

- Abrasion resistance
- Blade cut resistance
- Tear strength resistance
- Puncture resistance
- Cut Resistance method (EN ISO 13997)

TECHNICAL DATA

Description	13G HPPE cut resistant gloves, with black sandy palm coating,TPR on back				
Materials	Liner: HPPE knit				
	Coating: Sandy nitrile coated palm, TPR on back				
Cuff Style	Elastic seamless knit				
Color	white, grey, black, red, blue, etc.				
Size	7/S	8/M	9/L	10/XL	11/XXL
Length (cm)	/	24	25	26	27
Packing	Printing logo, 6 pairs per bag, 72 pairs per case				

Tolerance: ±5mm

STANDARDS

- CE CATEGORY: II Intermediary risk in accordance with:
- EN 420 / AS / NZS2161.2:2016 General Requirements
- EN 388 / AS / NZS2161.3:2016 Protection Against Mechanical Risks